

正方形角パイプ SUS304 サイズおよび断面性能

サイズmm (A×B)	肉厚 t mm	長さ mm	重量 kg/m	断面積 cm ²	断面二次 モーメント		断面係数		断面二次 半径		研 磨
					Ixcm ⁴	Iycm ⁴	Zxcm ³	Zycm ³	ixcm	iycm	
40×40	3	6,000	3.34	4.208	9.32	4.66	1.49	●●			
	4	6,000	4.24	5.348	11.1	5.54	1.44	●			
50×50	3	6,000	4.29	5.408	19.5	7.79	1.90	●●			
	4	6,000	5.51	6.948	23.7	9.49	1.85	●●			
	5	6,000	6.63	8.356	27.0	10.8	1.80	●			
60×60	3	6,000	5.24	6.608	35.1	11.7	2.31	●			
	4	6,000	6.78	8.548	43.6	14.5	2.26	●●			
	5	6,000	8.21	10.36	50.5	16.8	2.21	●			
75×75	3	6,000	6.67	8.408	71.6	19.1	2.92	●			
	4	6,000	8.68	10.95	90.2	24.1	2.87	●			
	5	6,000	10.6	13.36	106	28.4	2.82	●			
	6	6,000	12.4	15.63	120	32.0	2.77	●			
80×80	3	6,000	7.14	9.008	87.8	22.0	3.12	●			
	4	6,000	9.32	11.75	111	27.8	3.07	●			
	● 5	6,000	11.4	14.36	131	32.9	3.03	●			
90×90	3	6,000	8.10	10.21	127	28.3	3.53	●			
	4	6,000	10.6	13.35	162	36.0	3.48	●			
	● 5	6,000	13.0	16.36	193	42.9	3.43	●			
	● 6	6,000	15.3	19.23	220	49.0	3.39	●			
100×100	3	6,000	9.05	11.41	177	35.4	3.94	●			
	4	6,000	11.9	14.95	226	45.3	3.89	●			
	5	6,000	14.6	18.36	271	54.2	3.84	●			
	6	6,000	17.2	21.63	311	62.3	3.79	●			
	9	6,000	24.3	30.67	408	81.6	3.65	●			
110×110	3	6,000	10.0	12.61	238	43.3	4.35	●			
	4	6,000	13.1	16.55	306	55.6	4.30	●			
	● 5	6,000	16.1	20.36	368	66.9	4.25	●			
	● 6	6,000	19.1	24.03	424	77.2	4.20	●			
	● 9	6,000	27.2	34.27	564	102	4.06	●			
120×120	3	6,000	11.0	13.81	312	52.1	4.76	●			
	4	6,000	14.4	18.51	402	67.1	4.71	●			
	5	6,000	17.7	22.36	485	80.9	4.66	●			
	6	6,000	21.0	26.43	562	93.7	4.61	●			
	● 9	6,000	30.0	37.87	755	126	4.46	●			

正方形角パイプ SUS304 サイズおよび断面性能

サイズmm (A×B)	肉厚 t mm	長さ mm	重量 kg/m	断面積 cm ²	断面二次 モーメント		断面係数		断面二次 半径		研 磨
					Ixcm ⁴	Iycm ⁴	Zxcm ³	Zycm ³	ixcm	iycm	
125×125	3	6,000	11.4	14.41	355	56.7	4.96	●			
	4	6,000	15.0	18.95	457	73.2	4.91	●			
	5	6,000	18.5	23.36	553	88.4	4.86	●			
	6	6,000	21.9	27.63	641	103	4.82	●			
150×150	9	6,000	31.5	39.67	865	138	4.67	●			
	3	6,000	13.8	17.41	623	83.0	5.98	●			
	4	6,000	18.2	22.95	808	108	5.93	●●			
	5	6,000	22.5	28.36	982	131	5.89	●			
	6	6,000	26.7	33.63	1150	153	5.84	●			
175×175	9	6,000	38.6	48.67	1580	210	5.69	●			
	12	6,000	49.6	62.53	1920	257	5.55	●			
	3	6,000	16.2	20.41	1000	114	7.00	●			
	4	6,000	21.4	26.95	1300	149	6.95	●			
200×200	● 5	6,000	26.5	33.36	1590	182	6.91	●			
	● 6	6,000	31.4	39.63	1860	213	6.86	●			
	9	6,000	45.7	57.67	2600	297	6.71	●			
	12	6,000	59.1	74.53	3220	368	6.57	●			
250×250	3	6,000	18.6	23.41	1510	151	8.02	●			
	4	6,000	24.5	30.95	1970	197	7.97	●			
	5	6,000	30.4	38.36	2410	241	7.93	●			
	6	6,000	36.2	45.63	2830	283	7.88	●			
	9	6,000	52.9	66.67	3990	399	7.73	●			
300×300	12	6,000	68.6	86.53	4980	498	7.59	●			
	4	6,000	30.9	38.95	3910	313	10.0	●			
	5	6,000	38.4	48.36	4810	384	9.97	●			
	6	6,000	45.7	57.63	5670	454	9.92	●			
300×300	9	6,000	67.1	84.67	8090	647	9.78	●			
	12	6,000	87.7	110.5	10300	820	9.63	●			
	4	6,000	37.2	46.95	6830	455	12.1	●			
	5	6,000	46.3	58.36	8420	561	12.0	●			
	6	6,000	55.2	69.63	9960	664	12.0	●			
300×300	9	6,000	81.4	102.7	14300	956	11.8	●			
	12	6,000	107	134.5	18300	1220	11.7	●			

●は受注生産

※研磨品につきましては、各支店・営業所にご相談ください。

ステンレス溶接コラム

- 1.サイズはオーダーメイド、小ロット（1本ヨリ）短納期にて対応。
- 2.サイズ、用途により溶接は1シーム、2シーム、4シームとなります。

- 3.自動溶接（プラズマ、炭酸ガスアーク）にて溶接部の品質は均一。
- 4.SUS304、SUS304L、SUS316、SUS316Lをベースにて、他鋼種も取扱い可能。